


4. Battery Unit

Wire-to-Board



DF63
Positive Lock
Wire-to-Wire Available
Pitch : 3.96/7.92mm
No. of Pos. : 1-6
Applicable Cables :
16-22 AWG
Rated Current : 15A Max.



DF59M
Battery, Power
Low Profile, 1pos.
Rated Current :
6A Max.

Board-to-Board




FX30B
For Battery Power
Floating Design
Mated Height :
11.0mm
(Coplanar, Right Angle)
20-30 (Mezzanine)
No. of Pos. : 2-5
Rated Current : 25A Max.

Waterproof



HR30
Push-pull Type
IP67/IP68
Waterproof
No. of Pos. : 3-12
Applicable Cables :
26-30 AWG

FPC Connector



FH52K
For BMS
Bottom Contact
Front Flip
Height : 2.0mm
Pitch : 0.5/1.0mm
Depth : 5.7mm
No. of Pos. : 6-80
Rated Current : 0.5A



FH34
Top & Bottom Contact
Back Flip
Pitch : 0.5mm
Height : 1.0mm
Depth : 3.8mm
No. of Pos. : 4-50
Rated Current : 0.5A



FH62/FH72
One Action
For Display
Pitch : 0.25/0.3mm
Height : 1.1/0.9mm
Depth : 4.0/3.5mm
No. of Pos. :
13-61/11-31
Rated Current : 0.3A



FH63S
One Action
For Display
Pitch : 0.25/0.3mm
Height : 1.1/0.9mm
Depth : 5.15mm
No. of Pos. : 13-31
Rated Current : 0.5A