

2. Controller/Shift Lever

Wire-to-Board



DF13
 Mated Height : 5.8mm Max.
 Pitch : 1.25mm
 No. of Pos. : 2-15 (Single Row)
 10-40 (Double Row)
 Applicable Cables : 26-32 AWG
 Rated Current : 1.0A



DF57H
 For Battery, Low Profile, Snap Lock Design
 Mated Height : 1.4mm
 Pitch : 1.2mm
 Depth : 4.65mm
 No. of Pos. : 2-6
 Applicable Cables : 26-34 AWG
 Rated Current : 2.5A Max.



DF58
 For Battery, Low Profile, Snap Lock Design
 Mated Height : 1.0mm
 Pitch : 1.2mm
 Depth : 4.97mm
 No. of Pos. : 2-6
 Applicable Cables : 28-30 AWG
 Rated Current : 3A Max.

Waterproof



HR30
 Push-pull Type
 IP67/IP68
 Waterproof
 No. of Pos. : 3-12
 Applicable Cables : 26-30 AWG

Interface




CX
 USB Type-C
 IPX8, IPX4
 Waterproof

3. Front/Center/Rear Unit (Speed Sensor, Torque Sensor)

Wire-to-Board



DF57H
 Low Profile for Battery
 Snap Lock Design
 Mated Height : 1.4mm
 Pitch : 1.2mm
 No. of Pos. : 2-6
 Applicable Cables : 26-34 AWG
 Rated Current : 2.5A Max.



DF58
 Low Profile for Battery
 Snap Lock Design
 Mated Height : 1.0mm
 Pitch : 1.2mm
 Depth : 4.97mm
 No. of Pos. : 2-6
 Applicable Cables : 28-30 AWG
 Rated Current : 3A Max.

FPC Connector



FH34
 Top & Bottom Contact
 Back Flip
 Height : 1.0mm
 Pitch : 0.5mm
 Depth : 3.8mm
 No. of Pos. : 4-50
 Rated Current : 0.5A



FH62/FH72
 One Action, Display
 Pitch : 0.25/0.3mm
 Height : 1.1/0.9mm
 Depth : 4.0/3.5mm
 No. of Pos. : 13~61/11~31
 Rated Current : 0.3A